



Refrigeration

NEO Concept GN refrigerated cabinets

2/1 GN REFRIGERATED CABINET, CAF-1603 P

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.388,00	1.450,00
Depth	mm	826,00	850,00
Height	mm	2.008,00	2.150,00
Weight	Kg	213,00	220,00
Volumen	m3	2,30	2,65

ELECTRICITY

<u>Electric power</u>	KW	0,85
230V -1+N		2x1,5+T - 6 A
230V - III		
400V - III+N		

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION

R-134 a

Certificate EQNET- CE

SGS-2103-0906-1

2/1 GN REFRIGERATED CABINET, CAF-1603 P

Stainless steel exterior, except rear panel.
Stainless steel interior, with rounded corners at the bottom.
Stainless steel adjustable legs, .
Doors with automatic locking device, and fans stop when door is opened.
Internal shelves of plastic-coated steel, adjustable in height.
Operating voltage 220/240 V – I – 50 Hz.
N. of doors for refrigeration: 1 big door - 1 small door .
N. of doors for fish compartment: 1 small door.
Equipment: 7 shelves of plastic-coated steel and supports guides in stainless steel.
Capacity (litres): 1050 + 350
Total power: 851 W.
Dimensions: 1.388 x 826 x 2.008 mm.

REFRIGERATED COMPARTMENT:

Forced draught.
Copper evaporator with aluminium fins.
Independent R-134 A motor.
Removable, ventilated airtight compressor.
50-mm thick injected polyurethane insulation.
Density 40 kg. No CFC.
Operating temperature -2 °C, +8 °C at room temperature of 38°C.
Automatic evaporation of water during defrosting.
Illuminated general switch.
Internal lighting.
Electronic temperature and defrosting control and display.

FISH COMPARTMENT:

Capacity: 350 litres
Static refrigeration. Copper evaporator with aluminium fins.
Independent R-134 A motor.
Operating temperature -4°C, +2°C at room temperature of 38°C.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	200	5	1.840		Prever Interruptor diferencial

