



Refrigeration

NEO Concept GN refrigerated cabinets

2/1 GN REFRIGERATED CABINET, CAF-1604 P

DIMENSIONS

		Article	Packed
Length	mm	1.388,00	1.450,00
Depth	mm	826,00	850,00
Height	mm	2.008,00	2.150,00
Weigth	Kg	213,00	220,00
Volumen	m3	2,30	2,65

ELECTRICITY

Electric power	KW	
230V -1+N		0,85
230V - III		2x1,5+T - 6 A
400V - III+N		

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION

R-134 a

Certificate EQNET- CE

SGS-2103-0906-1

2/1 GN REFRIGERATED CABINET, CAF-1604 P

Stainless steel exterior, except rear panel.

Stainless steel interior, with rounded corners at the bottom.

Stainless steel adjustable legs, .

Doors with automatic locking device, and fans stop when door is opened.

Internal shelves of plastic-coated steel, adjustable in height.

Operating voltage 220/240 V – I – 50 Hz.

N. of doors for refrigeration: 3 small doors.

N. of doors for fish compartment: 1 small door.

Equipment: 7 shelves of plastic-coated steel and supports guides in stainless steel.

Capacity (litres): 1050 + 350

Total power: 851 W.

Dimensions: 1.388 x 826 x 2.008 mm.

REFRIGERATED COMPARTMENT:

Forced draught.

Copper evaporator with aluminium fins.

Independent R-134 A motor.

Removable, ventilated airtight compressor.

50-mm thick injected polyurethane insulation.

Density 40 kg. No CFC.

Operating temperature -2 °C, +8 °C at room temperature of 38°C.

Automatic evaporation of water during defrosting.

Illuminated general switch.

Internal lighting.

Electronic temperature and defrosting control and display.

FISH COMPARTMENT:

Capacity: 350 litres

Static refrigeration. Copper evaporator with aluminium fins.

Independent R-134 A motor.

Operating temperature -4°C, +2°C at room temperature of 38°C.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	200	5	1.840		Prever Interruptor diferencial

