



### Refrigeration

NEO Concept GN refrigerated cabinets

## 2/1 GN REFRIGERATED CABINET, CAF-802 P

#### DIMENSIONS

		Article	Packed
Length	mm	693,00	750,00
Depth	mm	826,00	850,00
Height	mm	2.008,00	2.150,00
Weigth	Kg	168,00	175,00
Volumen	m3	1,15	1,37

#### ELECTRICITY

Electric power	KW	
230V -1+N		0,55
230V - III		2x1,5+T - 6 A
400V - III+N		

#### WATER

Not used

#### GAS

Not used

#### STEAM

Not used

#### AIR

Not used

#### REFRIGERATION

R-134 a

#### Certificate EQNET- CE

SGS-2103-0906-1

#### 2/1 GN REFRIGERATED CABINET, CAF-802 P

Stainless steel exterior, except rear panel.  
Stainless steel interior, with rounded corners at the bottom.  
Stainless steel adjustable legs, .  
Doors with automatic locking device, and fans stop when door is opened.  
Internal shelves of plastic-coated steel, adjustable in height.  
Operating voltage 220/240 V – I – 50 Hz.  
N. of doors for refrigeration: 1 small door.  
N. of doors for fish compartment: 1 small door.  
Equipment: 4 shelves of plastic-coated steel and supports guides in stainless steel.  
Capacity (litres): 350 + 350.  
Total power: 552 W.  
Dimensions: 693 x 826 x 2.008 mm.

#### REFRIGERATED COMPARTMENT:

Forced draught.  
Copper evaporator with aluminium fins.  
Independent R-134 A motor.  
Removable, ventilated airtight compressor.  
50-mm thick injected polyurethane insulation.  
Density 40 kg. No CFC.  
Operating temperature -2 °C, +8 °C at room temperature of 38°C.  
Automatic evaporation of water during defrosting.  
Illuminated general switch.  
Internal lighting.  
Electronic temperature and defrosting control and display.

#### FISH COMPARTMENT:

Capacity: 350 litres  
Static refrigeration. Copper evaporator with aluminium fins.  
Independent R-134 A motor.  
Operating temperature -4°C, +2°C at room temperature of 38°C.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	200	5	1.840		Prever Interruptor diferencial

